



# HAULER<sup>®</sup> PRO LSV

## TAKING SUPERIOR PERFORMANCE FURTHER.

Expand your reach with the Cushman<sup>®</sup> Hauler PRO LSV which comes standard with impressive load capacity, a durable cargo box, and street legal capability. Built exclusively with an ELiTE<sup>®</sup> lithium drivetrain, powered by Samsung SDI technology, the Hauler PRO LSV is the ultimate work vehicle.

**ELiTE<sup>®</sup>**  
LITHIUM

**STREET LEGAL**  
FMVSS 500 & SAE  
J2358 CERTIFIED

**1200 LB**  
LOAD CAPACITY

**25 MPH**  
MAX SPEED

**ZERO MAINTENANCE**  
ELiTE LITHIUM BATTERY



# HAULER PRO LSV / ELiTE

## STREET LEGAL

### ELiTE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- 6.2 Triple Pack Battery Option for Extended Range

### STANDARD FEATURES

- Backup Camera
- Rear View Mirror with Integrated Display
- Pedestrian Warning System
- Maximum Speed of 25 MPH
- Lap Belts
- 4 Wheel Hydraulic Brakes
- Center High Mount Brake Light
- Large Fender Flares
- OPS (Operator Protective Structure) Rated Canopy Structure
- Side View Mirrors
- Turn Signals and Horn
- Dash with Versatile Storage Areas
- LED Headlights
- Brake Lights
- Limited Slip Differential
- Automatic Park Brake
- VIN number

### OPTIONS & ACCESSORIES

- IntelliGauge
- Differential Scuff Guard
- USB Port
- Lighted License Plate Holder
- Aluminum Bed
- Bed Dividers
- Reflective Safety Triangle
- Brush Guard
- Additional Body Colors
- Soft Enclosure

**CUSHMAN.COM**

### BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Forest Green

### DIMENSIONS

OVERALL LENGTH	119.75 in (304 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT W/ CANOPY	70.25 in (178 cm)
WHEEL BASE	75.5 in (191.77 cm)
FRONT WHEEL TRACK	37.25 in (94.615 cm)
REAR WHEEL TRACK	38.5 in (97.8 cm)
GROUND CLEARANCE	5.5 in (14 cm)
CARGO BOX CAPACITY	12 cu ft (0.34 cu m)
CARGO BOX DIMENSIONS	39 in (L) x 44 in (W) x 12 in (D) (99 cm x 111.8 cm x 30.5 cm)
CARGO BOX MATERIAL	Roto-Molded Polyethylene

### POWER

POWER SOURCE	56.7V Li-Ion Battery
MOTOR TYPE	AC Induction
HORSEPOWER (KW)	14.9 hp (11.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary
BATTERY (QTY/TYP)	4.2 ELiTE - Twin Pack
BATTERY CHARGER	811 Watt World Charger
KEY OR PEDAL START	Pedal
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Limited-Slip Differential with Helical Gears
SPEED CONTROLLER	350 Amp AC Controller
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse / Key Switch
REAR AXLE RATIO	16.99:1

### PERFORMANCE

SEATING CAPACITY	2-Person
CURB WEIGHT	1066 lb (480 kg) (Twin Battery Pack)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
BED LOAD CAPACITY	800 lb (363 kg)
TOWING CAPACITY	1500 lb (680 kg)
OUTSIDE CLEARANCE CIRCLE	21.4 ft (6.5 m)
SPEED	25 mph (40.2 kph)

### STEERING & SUSPENSION

STEERING	Self-Compensating Reduction Rack and Pinion
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers
BRAKES	Four-Wheel Hydraulic, Front Disk; Rear Self-Adjusting Drum
PARKING BRAKE	Automatic Electromagnetic
TIRES (FRONT & REAR)	Kenda K500 20 x 8-10" (6-ply Tires)