



ALL-NEW

HAULER[®] XL

EXCEL AT ANY JOB.

The Hauler XL gives operators the ability to carry more in a nearly 6-ft long bed while keeping the rugged durability that Hauler utility vehicles are known for. With two efficient, yet powerful, drivetrain options and street-legal LSV vehicle options, the Hauler XL is designed to help you get more out of your work day. Customize your vehicle with an aluminum cargo bed or steel drop side rails to make the most out of the 1200 lb bed load capacity.

ELITE[®]
LITHIUM

NEARLY 6 FT LONG
CARGO BED

1200 LB
CARGO BED CAPACITY

1600 LB
VEHICLE LOAD CAPACITY

STREET-LEGAL
CONFIGURATION

ELITE[®] LITHIUM
OR
13.5 HP
EFI GAS



ELITE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Multifunction SOC/Speedometer Gauge
- Automatic Park Brake
- Limited Slip Differential

OPTIONS & ACCESSORIES

- Street-Legal Configuration
- IntelliGauge™ (ELITE Only)
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Aluminum Cargo Bed
- Steel Drop Side Rails
- Long-Handled Tool Holders
- Radio Holder
- LED Headlights
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Hubcaps
- Hour Meter
- Limited Slip Differential
- Rapid On-Board Charger
- Fuel/Oil Gauge
- Custom Solutions Customization

CUSHMAN.COM

HAULER XL

ALL-NEW

	STREET-LEGAL HAULER XL LSV	HAULER XL ELITE	HAULER XL GAS
BODY & CHASSIS			
FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat		
BODY & FINISH	Injection Molded TPO		
VEHICLE COLORS	Forest Green, Patriot Blue, Bright White, Flame Red, Black		
DIMENSIONS			
OVERALL LENGTH	138.88 in (352.7 cm)		
OVERALL WIDTH	47.25 in (120 cm)		
OVERALL HEIGHT	72.25 in (183.5 cm) (w/ Canopy)	48.13 in (122.2 cm) (No Canopy) 70.25 in (178.4 cm) (w/ Canopy)	48.13 in (122.2 cm) (No Canopy) 70.25 in (178.4 cm) (w/ Canopy)
WHEEL BASE	93.25 in (236.9 cm)	93 in (236.2 cm)	93 in (236.2 cm)
WHEEL TRACK	37 in (94 cm) Front / 38.25 in (97.2 cm) Rear	34.13 in (86.7 cm) Front / 37.94 in (96.36 cm) Rear	34.13 in (86.7 cm) Front / 37.94 in (96.36 cm) Rear
GROUND CLEARANCE	6.25 in (15.9 cm)	5 in (12.7)	5 in (12.7)
CARGO FLAT BED DIMENSIONS	68.5 in (L) x 47.2 in (W) (174 cm x 120 cm)		
CARGO FLAT BED MATERIAL	Aluminum		
POWER			
POWER TRAIN	56.7V Li-Ion Battery	56.7V Li-Ion Battery	4-Cycle, 24.5 cu in (401cc)
HORSEPOWER (KW)	14.9 hp (11.1 kW) Peak	14.9 hp (11.1 kW) Peak	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPER)	4.2 Elite - Twin Pack	4.2 Elite - Twin Pack	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal		
AIR CLEANER	N/A	N/A	Replaceable Industrial Rated Dry Cartridge
FUEL CAPACITY	N/A	N/A	6.65 Gallon (25 L) Tank
DRIVE TRAIN	Motor Shaft Direct Drive	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears		
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse/ Key Switch	Dash Mount Forward-Neutral- Reverse/ Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	16.99:1	11.47: 1 (Forward) 14.35:1 (Reverse)
PERFORMANCE			
SEATING CAPACITY	2-Person (Bench)		
WEIGHT W/O BATTERIES	941 lb (427 kg)	863 lb (391 kg)	960 lb (435 kg)
CURB WEIGHT	1019 lb (462 kg)	940 lb (426 kg)	1000 lb (454 kg)
VEHICLE LOAD CAPACITY	1600 lb (726 kg)		
BED LOAD CAPACITY	1200 lb (544 kg)		
TOWING CAPACITY	1250 lb (567 kg)		
OUTSIDE CLEARANCE CIRCLE	26.81 ft (8.17 m)	18.9 ft (5.8 m)	18.9 ft (5.8 m)
SPEED	25 mph ± 0.5 mph (40.2 kph ± 0.8 kph)	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)
STEERING & SUSPENSION			
STEERING	Self-Compensating Rack and Pinion		
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers		
SERVICE BRAKE	Four-Wheel Hydraulic, Front Disk; Rear Self-Adjusting Drum	Dual Rear Wheel Mechanical Self-Adjusting Drum	Dual Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Automatic Electro-Magnetic	Automatic Electro-Magnetic	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	Load Star K399, 205/65-10 (6 Ply Tires)	Load Star K399, 215/60-8 (8 Ply Tires)	Load Star K399, 215/60-8 (8 Ply Tires)

Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model. California state law prohibits the sale of Model Year 2025 and later gas-powered golf carts. ©2024 Textron Specialized Vehicles Inc. 82821-G2 (Rev. 12/2024)

