

HAULER 1200X



GEARED UP TO CONQUER YOUR TO-DO LIST.

With a no-nonsense attitude, the Hauler® 1200X lends more than a hand on your toughest work days. Standard features include a lifted suspension, ergonomic seats and ample leg room that complement its smooth ride and rugged demeanor. From transporting equipment around your facility to watering down golf greens, the Hauler 1200X is a force to be reckoned with.

LET'S WORK.®

13.5HP EFI GAS **1200**LB TOW

12 CU FT CARGO BED

900LB

CAPACITY

BED LOAD CAPACITY





CUSHMAN HAULER 1200X









OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- L-Track Aluminum Bed System
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Brush Guard
- Rearview Mirror
- ROPS-Certified Cab

- · Ladder/Hoop Rack
- Brake Lights
- Tail Lights
 E-Shield™ Frame
 Fuel/Oil Gauge
- Premium Steering Wheel
- Side Body Color
- Windshield
- LED Headlights
- Glove Box
- Floor Mount Attachment

BODY & CHASSIS	
FRAME	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Patriot Blue, Forest Green
DIMENSIONS	
OVERALL LENGTH	119 in (302.3 cm)
OVERALL WIDTH	49.4 in (125.5 cm)
OVERALL HEIGHT W/CANOPY	77 in (195.6 cm)
WHEEL BASE	77.5 in (196.9 cm)
FRONT WHEEL TRACK	38.0 in (96.5 cm)
REAR WHEEL TRACK	38.5 in (97.8 cm)
GROUND CLEARANCE	7 in (17.8 cm)
CARGO BOX CAPACITY	12 cu ft (0.34 m³)
POWER	
POWER SOURCE	4-cycle, 24.5 ci (401cc)
VALVE TRAIN	Single Cylinder OHV
HORSEPOWER (KW)	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPE)	One 12V Maintenance Free
KEY OR PEDAL START	Pedal
AIR CLEANER	Replacable Dry Cartridge
LUBRICATION	Pressurized Oil System
OIL FILTER	Spin-On
COOLING SYSTEM	Air Cooled
FUEL CAPACITY	6.65 Gallon (25 L) Tank
DRIVETRAIN	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears
GEAR SELECTION	Forward-Reverse
REAR AXLE RATIO	11.47:1 (Forward) 14.35:1 (reverse)
PERFORMANCE	
SEATING CAPACITY	2 Person
CURB WEIGHT	1003 lb (455 kg)
BED LOAD CAPACITY	500 lb (227 kg)
VEHICLE LOAD CAPACITY	900 lb (408 kg)
SPEED	16.5 mph ± 0.5 mph (26.6 kph ± 0.8 kph)
TOWING CAPACITY	1200 lb (544 kg) max
OUTSIDE CLEARANCE CIRCLE	23.5 ft (7.2 m)
STEERING & SUSPE	NSION
STEERING	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement
FRONT/REAR TIRES	20 x 8.00 -10

www.cushman.com