



HAULER[®] 1200 SERIES

RELENTLESS POWER TO OVERCOME THE TOUGHEST TASKS.

The Hauler 1200 Series is equipped to handle any job on your course. A large bed providing essential functionality can easily be converted for any task. Featuring integrated tie-downs, a 12 cubic-foot cargo bed and higher ground clearance with the Hauler 1200X, transporting tools and supplies has never been easier. Your work is unforgiving, expect nothing less than the best with the Hauler 1200 Series.

13.5 HP
EFI GAS

12 CU FT
CARGO BED

1500LB / 1200LB
TOWING CAPACITY

1200LB / 900LB
LOAD CAPACITY



HAULER 1200

HAULER 1200X

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- 15 cu-ft Aluminum Bed with L-Track System
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Ladder/Hoop Rack (Aluminum Bed Only)
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Standard Rear Receiver Hitch
- Fuel/Oil Gauge
- Drop-In Refresher (Plastic Bed Only)

CUSHMAN.COM

HAULER® 1200 / SERIES

	HAULER 1200	HAULER 1200X
BODY & CHASSIS		
FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Forest Green	
DIMENSIONS		
OVERALL LENGTH	119 in (302 cm)	
OVERALL WIDTH	49.4 in (125.5 cm)	
OVERALL HEIGHT W/CANOPY	70.5 in (179.1 cm)	77 in (195.6 cm)
WHEEL BASE	76.8 in (195.1 cm)	77.5 in (196.9 cm)
FRONT WHEEL TRACK	35 in (88.9 cm)	38.0 in (96.5 cm)
REAR WHEEL TRACK	38.5 in (97.8 cm)	
GROUND CLEARANCE	3.5 in (8.9 cm)	7 in (17.8 cm)
CARGO BOX CAPACITY	12 cu ft (0.34 cu m)	
CARGO BOX DIMENSIONS	39 in (L) x 44 in (W) x 12 in (D) (99 cm x 111.8 cm x 30.5 cm)	
CARGO BOX MATERIAL	Roto-Molded Polyethylene	
POWER		
POWER TRAIN	4-Cycle, 24.5 cu in (401cc)	
VALVE TRAIN	Single Cylinder OHV	
HORSEPOWER (KW)	13.5 hp (10.1 kW)	
ELECTRICAL SYSTEM	Starter/Generator. Solid State Reg.	
BATTERY (QTY/TYPE)	One, 12V Maintenance Free	
KEY OR PEDAL START	Pedal	
AIR CLEANER	Replaceable Industrial Rated Dry Cartridge	
LUBRICATION	Pressurized Oil System	
OIL FILTER	Spin-On	
COOLING SYSTEM	Air Cooled	
FUEL CAPACITY	6.65 Gallon (25 L) tank	
DRIVE TRAIN	Continuously Variable Transmission	
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Forward - Reverse	
REAR AXLE RATIO	11.47: 1 (Forward) 14.35:1 (Reverse)	
PERFORMANCE		
SEATING CAPACITY	2-Person	
CURB WEIGHT	980 lb (445 kg)	1003 lb (455 kg)
BED LOAD CAPACITY	800 lb (363 kg)	500 lb (227 kg)
VEHICLE LOAD CAPACITY	1200 lb (545 kg)	900 lb (408 kg)
SPEED	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)	16.5 mph ± 0.5 mph (26.6 kph ± 0.8 kph)
TOWING CAPACITY	1500 lb (680 kg) max	1200 lb (544 kg) max
OUTSIDE CLEARANCE CIRCLE	21.5 ft (6.6 m)	23.5 ft (7.2 m)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Dual Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	18 x 8.5 - 8 (6 - Ply Tires)	20 x 8-10 (6 - Ply Tires)