



CUSHMAN®

SHUTTLE™ 6



TRANSPORT LARGE GROUPS EFFICIENTLY.

The Cushman® Shuttle™ 6 is your go-to vehicle for effectively moving people. With the combination of four-forward-facing seats and two rear-facing seats, you can safely transport up to six people comfortably throughout your facility. Available with the option of an energy efficient 72V AC electric drivetrain or a 13.5 hp EFI gas engine, the Shuttle 6 has the stamina necessary to take care of your personnel.

LET'S WORK.®

**13.5HP
EFI GAS**

**72V
AC ELECTRIC
DRIVETRAIN**

**6
PERSON
SEATING
CAPACITY**



CUSHMAN® SHUTTLE™ 6



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pinstripes
- Body Color (Forest Green, White or Custom Options)
- On Board Charger
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)
- Wheel Covers
- Limited Slip Differential
- Trail Tires



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

| | ELECTRIC MODEL | EFI GAS MODEL |
|----------------------------------|---|---------------------------------------|
| BODY & CHASSIS | | |
| FRAME | Welded Steel w/ DuraShield™ Powder Coat | |
| BODY & FINISH | Injection Molded TPO | |
| STANDARD COLOR | Patriot Blue | |
| DIMENSIONS | | |
| OVERALL LENGTH | 136.0 in (345 cm) | |
| OVERALL WIDTH | 48.5 in (123 cm) | |
| OVERALL HEIGHT | 48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof) | |
| WHEEL BASE | 93.5 in (237 cm) | |
| WHEEL TRACK | 34.2 in (87 cm) Front / 38.0 in (97 cm) Rear | |
| GROUND CLEARANCE | 4.3 in (11 cm) | |
| POWER | | |
| POWER SOURCE | 72V DC | 4-Cycle, 24.5 ci (401cc) |
| VALVE TRAIN | 22.4 hp (16.7 kW) Intermittent | Single Cylinder OHV |
| HORSEPOWER (KW) | 72V | 13.5 hp (10.1 kW) |
| ELECTRICAL SYSTEM | Six, 12 Volt Deep Cycle | Starter/Generator. Solid State Reg. |
| BATTERY CHARGER | 1000 Watt, 72V, 120/230V VAC UL Listed | One, 12V Maintenance Free |
| KEY OR PEDAL START | Pedal | |
| AIR CLEANER | N/A | Replacable Dry Cartridge |
| LUBRICATION | N/A | Pressurized Oil System |
| OIL FILTER | N/A | Spin-On |
| COOLING SYSTEM | N/A | Air Cooled |
| FUEL CAPACITY | N/A | 6 Gallon (22.7 L) Tank |
| SPEED CONTROLLER | 350 Amp AC | N/A |
| DRIVE TRAIN | Motor Shaft Direct Drive | Continuously Variable Transmission |
| TRANSAXLE | Differential w/ Helical Gears | |
| GEAR SELECTION | Dash-Mounted Forward-Neutral-Reverse | Forward - Reverse |
| REAR AXLE RATIO | 17:1 | 11.47:1 (Forward) 14.35:1 (Reverse) |
| PERFORMANCE | | |
| SEATING CAPACITY | 6-Person | |
| WEIGHT W/O BATTERIES | 964 lb (437 kg) | N/A |
| CURB WEIGHT | 1456 lb (660 kg) | 1164 lb (528 kg) |
| VEHICLE LOAD CAPACITY | 1200 lb (544 kg) | |
| OUTSIDE CLEARANCE CIRCLE | 25.5 ft (7.8 m) | 25.5 ft (7.8 m) |
| SPEED | 16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) (High Speed) | 14 mph ± 0.5 mph (22.5 kph ± 0.8 kph) |
| | 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed) | |
| STEERING & SUSPENSION | | |
| STEERING | Self-Compensating Rack & Pinion | |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers | |
| SERVICE BRAKE | Rear Wheel Mechanical, Self-Adjusting Drum | |
| PARKING BRAKE | Self-Compensating, Single-Point Engagement | |
| TIRES (FRONT & REAR) | 18 x 8.50 - 8 (4 Ply Rated) | |

www.cushman.com

©2019 Textron Specialized Vehicles Inc.
Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

82284-G7 (Rev. 12/2018)