



CUSHMAN®

STOCK CHASER™



BUILT FOR TIGHT SPACES AND HIGH PLACES.

The Stock Chaser™ is designed to work its way through narrow warehouse aisles, distribution centers and manufacturing facilities. Featuring a spacious cargo deck and a 1,000 lb. payload capacity, it's powered by a zero-emissions, 24V electric drivetrain. If you need a vehicle that can easily maneuver through the most demanding environments, rely on the Stock Chaser to get it done.

LET'S WORK.®

**4- OR 6-
STEP LADDER**
OPTIONS

24V
ELECTRIC
DRIVETRAIN

9.6 SQ FT
CARGO DECK
CAPACITY

CUSHMAN® STOCK CHASER™



9.6-SQ-FT CARGO DECK



ON-BOARD
BATTERY CHARGER

COMFORT GRIP STEERING

OPTIONS & ACCESSORIES

- Pintle or "E" Hitch
- Counterweight
- Cargo Deck (Galvanized)
- Cargo Deck (Stainless Steel)
- Headlights & Taillight
- Strobe Light (Ladder Required)
- Forward Motion Indicator
- Side Rails
- Hour Meter
- State-of-Charge Meter
- Ladder - 4 Step (Counterweight included)
- Ladder - 6 Step (Counterweight included)



COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY

BODY & CHASSIS

FRAME	Welded Steel w/ DuraShield™ Powder Coat
BODY & FINISH	Diamond Plate Poly Primer and Acrylic
STANDARD COLOR	Safety Yellow

DIMENSIONS

OVERALL LENGTH	88.4 in (225 cm)
OVERALL WIDTH	29.5 in (75 cm)
OVERALL HEIGHT	48.0 in (122 cm) (w/o Ladder) 78.0 in (198 cm) (w/ 4-step Ladder) 97.0 in (246 cm) (w/ 6-step Ladder)
WHEEL BASE	48.3 in (123 cm)
WHEEL TRACK	N/A Front / 24.75 in (63 cm) Rear
GROUND CLEARANCE	4.0 in (10 cm)
CARGO DECK CAPACITY	750.0 lb (340 kg)
CARGO DECK MATERIAL	Plywood

POWER

POWER SOURCE	24V DC Series Wound
HORSEPOWER (KW)	8.94 hp (6.67 kW) @ 1490 rpm
ELECTRICAL SYSTEM	24V
BATTERY (QTY/TYPER)	Four, 6V Deep Cycle
BATTERY CHARGER	24V DC, 100-240V AC On-Board, UL & CE
KEY OR PEDAL START	Pedal
SPEED CONTROLLER	Solid State 275 Amp Rated
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	14.78:1

PERFORMANCE

SEATING CAPACITY	1-Person (Standing)
WEIGHT W/O BATTERIES	522 lb (237 kg)
CURB WEIGHT	810 lb (367 kg)
VEHICLE LOAD CAPACITY	1000 lb (454 kg)
BED LOAD CAPACITY	750 lb (340 kg)
TOWING CAPACITY	Normal Draw Bar: 60 lb (27.2 kg) / Max Draw Bar Pull: 715 lb (324 kg)
OUTSIDE CLEARANCE CIRCLE	12.4 ft (3.8 m)
SPEED	8.5 mph max (13.7 kph max)

STEERING & SUSPENSION

STEERING	Direct Chain & Linkage
SUSPENSION	Solid (Front & Rear)
SERVICE BRAKE	Rear Wheel Mechanical Drum
PARKING BRAKE	Automatic
TIRES (FRONT & REAR)	4.80 x 8 (Load Range B)

www.cushman.com

©2016 Textron Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82328-G7 (Rev. 01/2016)