



CUSHMAN®

TITAN® XD



MEET THE REAL INDUSTRY GIANT.

Equipped with AC and IntelliBrake™ technology, the Titan XD offers increased energy efficiency and greater range, ready to conquer your longest days. A large cargo deck offers 3,000 pounds of hauling power and its impressive 8,000 lb towing capacity makes no task off limits. So take the burden out of your day and let the Titan XD carry the load.

LET'S WORK.®

48V
AC ELECTRIC
POWERTRAIN

2 & 4
PASSENGER
MODELS

8000LB
TOWING
CAPACITY



2-PASSENGER



4-PASSENGER

CUSHMAN® TITAN® XD



HALOGEN HEADLIGHTS



FUNCTIONAL DASH

OPTIONAL TURN SIGNALS



OPTIONAL PINTLE HITCH

OPTIONS & ACCESSORIES

- Non-Marking Tires
- Front & Rear Bumper
- Hard Cab (w/ or w/out Doors)
- Pintle Hitch (requires rear bumper)
- Clevis Hitch (requires rear bumper)
- Custom Color
- Headlights (LED)
- Turn Signals

| | 2-PASSENGER | 4-PASSENGER |
|----------------------------------|--|---|
| BODY & CHASSIS | | |
| FRAME | Welded Steel with DuraShield™ Powder Coat | |
| BODY & FINISH | Diamond Plate Patterned, Poly Primer & Acrylic | |
| STANDARD COLOR | Yellow | |
| DIMENSIONS | | |
| OVERALL LENGTH | 114.0 in (290 cm) | |
| OVERALL WIDTH | 44.5 in (113 cm) | |
| OVERALL HEIGHT | 47.0 in (119 cm) | |
| HEIGHT W/ OPTIONAL CAB | 72.0 in (183 cm) | |
| WHEEL BASE | 67.0 in (170 cm) | |
| FRONT WHEEL TRACK | 38.0 in (96.0 cm) | |
| REAR WHEEL TRACK | 38.0 in (96.0 cm) | |
| GROUND CLEARANCE | 5.0 in (12 cm) | |
| CARGO DECK CAPACITY | 41.5 in (105) W x 75 in (191 cm) L | 4.75 (12.1 cm) at Differential |
| CARGO DECK MATERIAL | Weather Proof Deck Board | |
| POWER | | |
| POWER SOURCE | 48-Volt DC | |
| HORSEPOWER (KW) | 16.8 HP (12.5 kW) Peak | |
| ELECTRICAL SYSTEM | 48-Volt | |
| BATTERY (QTY/TYPE) | Eight, 6-Volt Deep Cycle, Swing Out | |
| BATTERY CHARGER | 48V On-Board, 120/240 VAC UL | |
| KEY OR PEDAL START | Pedal Start | |
| SPEED CONTROLLER | 450 Amp AC | |
| DRIVE TRAIN | Motor Shaft Direct Drive | |
| TRANSAXLE | Differential with Helical Gears | |
| GEAR SELECTION | Dash Mounted Forward-Neutral-Reverse | |
| REAR AXLE RATIO | 17:1 | |
| PERFORMANCE | | |
| SEATING CAPACITY | 2-Person | 4-Person |
| WEIGHT W/O BATTERIES | 1260 lb (572 kg) | 1225 lb (560 kg) |
| CURB WEIGHT | 1756 lb (796 kg) | 1720 lb (780 kg) |
| VEHICLE LOAD CAPACITY | 3000 lb (1361 kg) | |
| CARGO DECK LOAD CAPACITY | 2600 lb (1179 kg) / 1600 lb (726 kg) EE | 2200 lb (998 kg) / 1200 lb (544 kg) EE |
| TOWING CAPACITY | 8000 lb (3628 kg) | |
| OUTSIDE CLEARANCE CIRCLE | 21.25 ft (6.47 m) | |
| INTERSECTING AISLE CLEARANCE | 84.0 ft (213 cm) | |
| SPEED | 14 mph +/- 0.5 mph (21 kph +/- 0.8 kph) / Tow Mode: 5 mph +/- .5 (8.1 kph +/- .8) | |
| STEERING & SUSPENSION | | |
| STEERING | Rack and Pinion | |
| FRONT SUSPENSION | Independent, Transverse Leaf Spring, Shocks | |
| REAR SUSPENSION | Leaf Springs & Shock Absorbers | |
| SERVICE BRAKE | Front Hydraulic Disc, Rear Hydraulic Drum | |
| PARKING BRAKE | IntelliBrake™ Automatic Parking Brake | |
| FRONT/REAR TIRES | 5.70 x 8 (Load Range C) | |

www.cushman.com

©2018 Textron Specialized Vehicles Inc. All rights reserved.
800.241.5855

82324-G4 (Rev. 07/2018)