

LIVE LARGER



EXPRESS™ S6



72 -VOLT AC
ELECTRIC

13.5-HP GAS ENGINE
WITH CLOSED LOOP EFI

CONVERTIBLE
REAR SEAT

EXPRESS™ S6



ELECTRIC

GAS

ELEVATE YOUR EXPECTATIONS.

Rediscover the moments that take your breath away with the E-Z-GO® Express S6. The Express S6 has room for 6 to embark on your effortless adventures. With a choice of a 72-volt powertrain that offers unparalleled power or an efficient 13.5 closed-loop EFI gas powertrain, the Express S6 will take you on a getaway you'll never forget. Escape reality with the vehicle that will make the life you've earned even more satisfying.

KEY FEATURES

- 18-in street tires
- 82-in top
- Front brush guard
- Dashboard storage pockets
- Headlights, taillights and brake lights
- Dual USB ports
- Fold-down windshield
- 72-volt AC powertrain (Electric Only)
- State of charge meter (Electric Only)
- Rabbit/Turtle Speed Switch (Electric Only)
- Low Oil Indicator (Gas Only)
- Fuel gauge (Gas Only)

DIMENSIONS

OVERALL LENGTH	143.5 in. (364 cm)
OVERALL WIDTH	49 in (124 cm)
OVERALL HEIGHT (W/O ROOF)	48.8 in (124 cm)
OVERALL HEIGHT (W/ ROOF)	72 in (183 cm)
WHEEL BASE	93.5 in (237 cm)
FRONT WHEEL TRACK	37.5 in (97 cm)
REAR WHEEL TRACK	38.5 in (98 cm)
GROUND CLEARANCE @ DIFFERENTIAL	5 in (18 cm)

POWER

POWER SOURCE	72 Volts AC	4 Cycle 24.5 cu in (401 cc)
VALVE TRAIN	N/A	Single Cylinder OHV
MOTOR TYPE	AC Induction	N/A
FUEL SYSTEM	N/A	Closed-Loop Electronic Fuel Injection
HORSEPOWER (KW)	22.4 hp (16.7 kW) Peak	13.5 hp (10.1 kW) Exceeds SAE J1940 Std
ELECTRICAL SYSTEM	72 Volt	Starter/Generator - Solid State Regulator
BATTERIES (QTY./TYPE)	Six, 12 Volt Deep Cycle	One, 12 Volt Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) Tank
BATTERY CHARGER	72 VDC Delta Q, 120/230 VAC, UL & CSA	N/A
SPEED CONTROLLER	350 Amp AC	N/A
DRIVETRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse	
REAR AXLE RATIO	17:1	11.47:1 (Forward); 14.35:1 (Reverse)

PERFORMANCE

SEATING CAPACITY	6-Passenger	
DRY WEIGHT	964 lbs. (437 kg)	1042 lb (473 kg)
CURB WEIGHT	1456 lb (660kg)	1077 lb (489 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)	
OUTSIDE CLEARANCE CIRCLE	32.5 ft. (9.9 m)	
SPEED (LEVEL GROUND)	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	16.0 mph ± 0.5 mph (25.7 kph ± 0.8 kph)

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion	
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single Point Engagement	
TIRES	SpeedRacer Tires 18 x 10 - 10, Diamond Wheel	Street Tires 18x10-10, Diamond Pattern Spoke Wheels

BODY & CHASSIS

FRAME	Welded Steel with Powder-Coat Protection	
BODY & FINISH	Injection Molded TPO	
AVAILABLE BODY COLORS	Almond, Black, Electric Blue, Flame Red, Inferno Red, Metallic Charcoal, Ocean Grey, Platinum, White	
AVAILABLE SEAT COLORS	Gray, Oyster, Tan, Black	



LIVE LARGER



www.ezgo.com

Features and specifications of vehicles subject to change without notice. Vehicles as photographed may include options not included on base model. ©2020 Textron Specialized Vehicles Inc. 82299-G11 (Rev. 02/2020)

